

EZ-Flash

EZ-Flash is a 23-mil self-adhering waterproofing membrane that is designed to provide superior air and vapor protection for windows and doors. Developed specifically for the multi-family and residential construction markets, EZ-Flash is a cold-applied system that offers excellent adhesion and easy application to a wide range of substrates including concrete, masonry, gypsum, steel and wood. EZ-Flash is available in 4", 6", 9" and 12" x 75' rolls.



Residential and Commercial Product Lines

About Carlisle WIP Products

As a division of Carlisle Construction Materials Incorporated, Carlisle WIP Products manufactures premium construction products for steep-slope and low-slope residential and commercial applications.



Carlisle WIP Products

1285 Ritner Highway • Carlisle, PA 17013

888.717.1440

www.carlislewipproducts.com



Water and Ice Protection



Water and Ice Protection (WIP®) self-adhering roofing underlayments offer an ideal solution for protecting against water and ice damming while withstanding some of nature's most unfavorable weather conditions. WIP is manufactured and backed by Carlisle, a leader in the roofing industry for more than 50 years.

Refer to Carlisle's data sheets to obtain applicable limitations for these products.



WIP 100 Granular Surface

- Strong underlayment for use on critical roof areas such as eaves, ridges, valleys, dormers and skylights
- 55-mil flexible, rubberized asphalt, fiberglass-reinforced membrane with a granular surface provides maximum skid resistance
- Easy application with split-release film
- UL Classified; FL #6785; ICC-ES ESR 1556; Miami-Dade Approved, ASTM D1970, International Building Code
- 30-day exposure time

WIP 100SG Summer Grade

- Summer Grade formulated especially to maintain consistency at high-ambient temperatures
- Strong underlayment for use on critical roof areas such as eaves, ridges, valleys, dormers and skylights
- 55-mil flexible, rubberized asphalt, fiberglass-reinforced membrane with a granular surface provides maximum skid resistance
- Easy application with split-release film
- UL Classified; FL #6785; ICC-ES ESR 1556; Miami-Dade Approved, ASTM D1970, International Building Code
- 30-day exposure time

WIP 250HT Multi-Purpose/High Temp

- Dual-barrier protection membrane designed to resist temperatures up to 250°F and ideal for use under metal and mechanically attached tile roofs
- 62-mil rubberized asphalt, fiberglass-reinforced membrane
- Easy application with split-release film
- UL Classified; FL #6785; ICC-ES ESR 1556, Miami-Dade Approved, ASTM D1970, International Building Code
- 90-day exposure time

WIP 300HT High Temperature

- High-temperature underlayment designed to resist temperatures up to 250°F and ideal for use under metal, including copper, zinc and COR-TEN®*; can also be used under synthetic, concrete and clay tiles and asphalt shingles
- 40-mil membrane comprised of a strong, skid-resistant polyolefin film laminated to a thick layer of highly adhesive rubberized asphalt
- Easy application with split-release film
- UL Classified; FL #6785; ICC-ES ESR 2206, Miami-Dade Approved, ASTM D1970, International Building Code
- 60-day exposure time (black); 120-day (white)

WIP 401LT Low Temperature

- Designed for low-temperature applications where the ambient temperature is between 30°F and 70°F (-1.1°C and 21.1°C)
- 40-mil membrane comprised of a strong, skid-resistant polyolefin film laminated to a thick layer of highly adhesive rubberized asphalt
- Easy application with split-release film
- UL Classified; ICC-ES ESR 2206
- 2009 and 2012 International Building Code™
- Meets ASTM D1970
- 60-day exposure time

*Contact technical department for installation instructions.